


*Asha*  
 Asha Sharma  
 Chapter Coordinator  
 Asha Cornell



Upto Ground floor top.

Sl.No.	Description.	Unit.	Quantity.	Rate./Unit.		Amount.	
				Rs.	P.	Rs.	P.
1	R.C.concrete (1:1.5:3) with graded stone chips (20 mm. down) excluding shuttering and reinforcement. (1 cement : 1.5 sand : 3 stone chips 20mm down).	cum.	6.25	2,690.00		16,812.50	
2	Reinforcement for reinforced concrete work in all sorts of structures including stirrups, binders etc. including supply of rods, initial straightning and removal of loose rust (if necessary) cutting to requisite length, hooking and bending to correct shape, placing in proper position and binding with 16 gauge black annealed wire at every inter-section, complete as per drawing and direction.	Mt.	0.80	20,831.00		16,664.80	
3	Hire and labour charges for shuttering with centering and necessary staging upto 4 m. using approved stout props and thick hardwood planks of approved thickness with required bracing for concrete slabs, beams, columns, lintels, curved or straight including fitting, fixing and striking out after completion of work. Above 30 mm. to 37 mm. thk. wooden shuttering.	sqm.	19.36	110.00		2,129.60	
4	Brick work with 1st. Class bricks in cement mortar (1:5).	cum.	7.00	1,747.50		12,232.50	
5	125 mm. thick brick work with 1st. Class bricks in cement mortar (1:4).	sqm.	25.67	230.00		5,904.10	
6	75 mm. thick brick work with 1st. Class bricks set in cement mortar (1:4) including H.B. netting in every alternate layer.	sqm.					
7	Plaster with sand and cement mortar including rounding off and chamfering corners as directed and raking out joints or roughening of concrete surface by chamfering etc. including throating, nosing and drip course where necessary.						
	i)With 1:6 cement mortar. 20 mm. thick.	sqm.	94.35	52.00		4,906.20	
	ii)With 1:6 cement mortar. 15 mm. thick.	sqm.	48.65	45.00		2,189.25	

*Asha*

*Asha Sharma  
Chapter Coordinator  
Asha Cornell*



Sl.No.	Description.	Unit.	Quantity.	Rate./Unit.		Amount.	
				Rs.	P.	Rs.	P.
	iii) With 1:4 cement mortar. 10 mm. thick.	sqm.	25.09	42.00		1,053.78	
8	White washing / colour washing including cleaning and smoothing surface thoroughly (5 parts of stone lime and one part of shell lime should be used in the finishing coat). Three coats.	%sqm.	119.44	430.00		513.59	
9	Snow cem on outer surface of the wall including cleaning and smoothing surface Two coats.	sqm.	48.65	11.00		535.15	
10	Sal wood work in door frame fitted and fixed with com- plete including a protective coat of painting at the con- tact surface of the frame.	cum.	0.80	28,980.00		23,184.00	
11	19 mm. thick panel (made of single plank) of door and window shutters with 1st. Class Indian teak.	sqm.	4.20	910.00		3,822.00	
12	M.S. works in framed gratings of round or square bars and frame work of M.S. flats (with the bars securedly fixed to the flat bar frame) with or without intermediate flat bar stiffner and fixed with necessary screws etc. complete as directed. (av. 17 Kg. per sqm.)	sqm.	4.32	408.42		1,764.37	
13	Supplying best Indian sheet glass panels set in putty and fitted and fixed with nails and putty complete. 3 mm. Thick (weighing 7.4 kg./sqm.).	sqm.	3.89	324.00		1,260.36	
14	Painting with best quality synthetic enamel paint of approved make and brand including smoothing surface by sand papering etc. including using of apprved putty etc. on the surface, if necessary.						
	i) on timber surface (hi-gloss) Two coats (with any shade)	sqm.	4.20	35.20		147.84	
	ii) On steel surface. (hi-gloss) Two coats (with any shade)	sqm.	8.64	28.60		247.10	